

HP LaserJet Pro 4003dn Duplex, Network Laser Printer

Хэвлэх хурд	Up to 42 ppm (A4, Draft)
Үйлдэл	Print
Ар өвөргүй хэвлэх	Automatic (standard)
Duty cycle (monthly, A4)	Up to 80,000 pages (Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Color LaserJet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups.)
Зард хэвлэвэл зохих хэмжээ	750 to 4000 pages
Print quality black (best)	Up to 1200 x 1200 dpi
Duplex Printing	Automatic
Холболт	1 Hi-Speed USB 2.0; 1 host USB at rear side; Gigabit Ethernet 10/100/1000BASE-T network; 802.3az(EEE)
Дэлгэц	2-line back lit LCD graphic display
Санах ой	256mb
Дэмжих үйлдлийн систем	Windows 11; Windows 10; Android; iOS; Mobile OS; macOS 10.15 Catalina; macOS 11 Big Sur; macOS 12 Monterey; Chrome OS
Paper handling input, standard	100-sheet multipurpose Tray 1, 250-sheet input Tray 2
Paper handling output, standard	150-sheet output bin
Хэвлэх хэмжээ	Paper (plain, EcoFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels
Media sizes, custom	Tray 1: 76 x 127 to 216 x 356 mm; Tray 2, optional Tray 3: 104.9 x 148.5 to 2165.9 x 356.6 mm
Тэжээл	110-volt input voltage: 110 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz)
Хэмжээ	381 x 357 x 216 mm
Жин	8.56 kg
Тохирох хор	HP 151A Black Original LaserJet Toner Cartridge (~3,050 pages), W1510A; HP 151X Black Original LaserJet Toner Cartridge (~9,700 pages), W1510X Non-Operating Humidity Range - 5 to 90% RH (non-condensing) Operating Humidity Range - 15 to 80% RH (non-condensing)
Ажиллах нөхцөл	Storage Temperature Range - -40 to 60°C Operating Temperature Range - 5 to 40°C Recommended Operating Temperature Range - 15 to 30°C