

Santak CASTLE C3K On-Line 3000VA/2700W Tower UPS

Santak CASTLE C3K On-Line 3000VA/2700W Tower UPS

Power rating	3000VA/2700W
Input	Input Voltage Range: (100-300)VAC Frequency Range: 40-70 Hz Input Power Factor: ≥ 0.99
Output	Nominal Output Voltage: 220/230/240VAC Frequency Range: 50$\pm$0.05Hz (Battery mode) Output Power Factor: 0.9 Voltage Regulation: 1% Outlet: IEC C13*4+C19*1 Current Crest Ratio: 3:1 Voltage Distortion (T HDv): < 1% @ linear load, < 5%@ non-linear load Output Waveform: Pure sine wave
Efficiency	Inverter Mode: >91% ECO Mode: >97%
Battery	Battery Type: 12V / 9Ah Number of Internal Battery: 6 Rated Battery Voltage: 72V Backup Time (@ FullLoad): > 3.5 mins Recharge Time (t o 90%): 4 hours Charging Current: 1.5A

	Battery Mode<-- >InverterMode: 0ms
Transfer Time	Inverter Mode<-- >BypassMode 4ms (typical)
Display	LED: load rating / battery capacity / input / output / operating mode
Interface	RS232: IEC model and UNIVERSAL model: RS232; SCHUKO model and SCHUKO/NEMA adaptable model: USB+EPO, no RS232 Communication Slot: Yes, comply optional cards NMC, CMC, AS400 card
Environment	Operating Temperature: 0~40°C Noise Level 1: <40dB@1 meter
Net Weight	22.7 kg
Dimension (W*D*H)	190x327x399mm